

Technical data:

Lane closure trailer		ZPP-2
Chassis and equipment:		
Type / weight / capacity:	AP 1300 / 1300 / 650 kg - basis chassis	
Dimensions (L x W x H):	4000 x 2200 x 4050 mm - without rotation lights	
Wheels:	14 / 185 R14 x (2 + 1)	
Trailer hitch:	Ø 50 - globular / Ø 40 - thorn	
Brakes:	running - inertial / parking - mechanical	
Electrical installation; voltage; connection:	ECE R 48.1; 12 - 24 V with TLC 2412S; ISO 1724	
Battery; charger; cable-reel:	12 V / 143 Ah ; ADP 400; 10 m - 3 x 1,5 mm ²	
Hydraulic pump; lifting consumption; elevation time:	12 V DC / 600 W; 7 A; < 30 sec	
Overall temperature range:	-30 .. +50 °C	
Signaling panels:		
LED arrow; width / leg; light intensity seg. / arrow; f. v. angle:	yellow; 210 / 1000 mm; > 2 / > 30 kcd (EN 12352 -L9H); 28°	
Voltage / consumption:	10 - 15 V DC / 3,5 A	
Flashing lights / consumption:	Ø 340 mm, with shade; 12 V DC / 1 A	
Rotating lights:	12 V DC / 1,2 A	
Arrow-sign rotating motor; rotating time:	40 VDC / 0,3 A; 20 s	
Reflecting foil:	type III - Diamond grade	
Dimensions UP/LO (W x H):	2200 x 1650 mm / 2200 x 2000 mm	